PureMatte



IMPRESS PANELS - HARMONY OF AESTHETICS AND FUNCTION

PUREMATTE MEETS TALNT TECHNOLOGY

TALNT Technology:

What's the difference between **PureMatte HPL** and standard HPL? PureMatte High Pressure Laminate (HPL) utilises advanced TALNT technology, resulting in an ultra-hardwearing surface with exceptional performance qualities:

Specially hardened using electronic beam curing (EBC), as PureMatte reaches the final stage of the manufacturing process, it is hit with electrons to create a unique hardened surface, making it suitable for both horizontal and vertical applications.

- + Scratch Resistance
- + Stain Resistance
- + Chemical Resistance
- + Anti-Bacterial Surface
- + Food Grade
- + Anti-fingerprint
- + Soft Matte Finish

Ideal for both horizontal and vertical applications, PureMatte is compatible with plywood and MDF, and is Greenguard certified. Matching ABS Edge is available.

Typical Uses:

Wall cladding, ceiling cladding, doors, staircases, kitchen furniture, bench tops and cabinets, bathroom furniture and cabinets, home furniture, retail furniture, hotel and restaurant furniture, laboratories, operating theatres, and in hospitals.

HEALTHCARE HOSPITALITY RESIDENTIAL Hospitals Hotels Kitchens Clinics Restaurants Bathrooms Laboratories Bars Tables Pharmacies Food Service Cabinetry	CHILD CARE Schools Preschool Restrooms Art rooms
---	--

COMMERCIAL Office fitout Furniture Counters & retail fitout Commercial kitchens Restrooms Cleanrooms & Labs


Colours:

Available in 11 classic colours, PureMatte creates aesthetically pleasing interior surfaces that look and feel clean and modern.

FRONT COVER: PUREMATTE RAVEN, NICOLA ROSS DESIGN, WWW.NICOLAROSSDESIGN.CO.NZ










When viewed under a microscope, you can see that the structure of PureMatte is like a landscape with uneven peaks and valleys. When light waves hit the surface, the angle of incidence is not the same everywhere. Therefore, light reflects in different directions. This is what makes PureMatte matt.




FINISHES

PUREMATTE RAVEN, KITCHENS BY GERMAN KITCHENS LTD WWW.GERMANKITCHENS.NZ

0

11 Jaco

COLOURS			
RAVEN		DOVE	CHAMPAGNE
			TRUFFLE
ATLANTIC			
ROYAL	RIVERSTONE		MILFORD



PUREMATTE AVAILABILITY GUIDE

Colour	Matching HPL Backer	Smooth	Woodgrain	Textile
Dove	\checkmark	\checkmark	\checkmark	\checkmark
Champagne	\checkmark	\checkmark	\checkmark	\checkmark
Truffle	\checkmark	\checkmark	\checkmark	\checkmark
Сосоа	\checkmark	\checkmark	\checkmark	\checkmark
Milford	\checkmark	\checkmark	\checkmark	\checkmark
Mist	\checkmark	\checkmark	\checkmark	\checkmark
Shadow	\checkmark	\checkmark	\checkmark	\checkmark
Royal	\checkmark	\checkmark	\checkmark	\checkmark
Atlantic	\checkmark	\checkmark	\checkmark	\checkmark
Riverstone	\checkmark	\checkmark	\checkmark	\checkmark
Raven	\checkmark	\checkmark	\checkmark	\checkmark

All colours available with colour matched backing Surfreme HPL

PUREMATTE SUBSTRATE CHART

		Panel size			Board thicknesses (mm)								
					10	12	15	16	18	21	24	25	30
MDF	Standard	2440x1220	6	EO		\checkmark	\checkmark	\checkmark	\checkmark	\checkmark		\checkmark	✓
		3660X1220	6	EO		\checkmark		\checkmark	\checkmark			\checkmark	\checkmark
	Moisture Resistant	2440x1220	6	EO		√		√	√			√	~
MDF FR	Moisture Resistant	2440x1220		EO		\checkmark			\checkmark				
Resistan	Resistant	3660x1220		EO		√							
Plywood Birch Meranti BS1088 Light weight Poplar	Birch	2440x1220		El					\checkmark		\checkmark		
	2440x1220		EO	✓	√	√		✓		√			
	weight	Preorder		E1					~				
								ģ	6	Enviro	nmental	l choice	
								E	E0/E1	Formaldehyde emission level			
									✓	Availa	ble		



ANTI-BACTERIAL PROTECTION

ISO22196 tested to kill 99.99% of bacteria in 24 hours

PureMatte provides peace of mind with spectacular anti-bacterial properties.

Testing by the Fraunhofer Institute for Manufacturing Technology and Advanced Materials in Germany to ISO 22196-2011 using Escherichia coli, Staphylococcus aureus, Salmonella cholearesius, and Pseudomonas aeruginosa organisms, concluding...

"the surface coating had very high antimicrobial activity (R >3) for all bacteria tested, with more than 99.99% of the original bacteria no longer detectable after a 24hr contact time."

FOOD SAFE

PureMatte has been certified by European testing laboratory, ISEGA, as food safe and suitable for use in food processing facilities, in accordance with European Standards EN1186, EN13130 and CEN/TS14234. Their certification states...

"...the sample material submitted may be used safely as a coating for HPL plates in food processing factories and may stand in direct contact with all kinds of foodstuffs as far as no hygiene requirements are violated".

ANTI-SCRATCH

To demonstrate its scratch-resistance we took to PureMatte with steel wool, a fork, and a key. Visit www. impresspanels.co.nz to see the results.

The PureMatte surface is hardened with advanced TALNT Technology which renders it extremely robust and resistant to scratching.

PureMatte achieves a scratch resistance of >3N in accordance with EN438-3 and therefore can be used without restriction in horizontal areas such as tables, desks and worktops.

STAIN-RESISTANCE

To demonstrate how incredibly stain-resistant PureMatte is we left red wine, beetroot juice, coffee, tea, curry powder and turmeric powder on PureMatte for 3 days. It all simply wiped clean with nothing more than a damp cloth and a melamine sponge.

We have also removed permanent marker and ball-point pen without trace using a damp melamine sponge.

Visit www.impresspanels.co.nz to see the stain test video or ask us to send you a sample and you can try it for yourself!

THERMO MICRO-HEALING

Because of TALNT Technology, PureMatte HPL can using thermal self healing to rapair micro scratches.

How to heal:

- 1. Place a damp cloth/rags directly on the scratches.
- 2. Apply heat on the cloth with an iron for 10-15 seconds.
- OR
- 1. Use a melamine sponge (Magic Eraser) to create friction on the surface.

2. Rub for approx 20 seconds until the scratches heal.

COLOUR CORE

PureMatte comes with colour core as standard. This means that the colour you see on the surface continues throughout the thickness of the HPL.

This gives an appealing edge detail when in an exposed edge application (such as on decorative plywood) you won't see any unsightly brown kraft layers that you get with standard HPL and also means if something sharp impacts the PureMatte surface and digs through the colour layer into the core, the same colour will be visible throughout the indentation or scratch, making it far less likely the damage will be noticeable



PureMatte

For further information and technical specifications visit

www.impresspanels.co.nz

Available with colourmatched ABS edging, PureMatte® is able to come ready to install. Using carbide tipped tools, you can saw, rout, and drill PureMatte®.

The colours and details shown in this brochure are as accurate as possible, however should only be used as an indication. Please refer to PureMatte[®] product swatches for actual colours.

> PureMatte® is marketed and distributed by Impress Panels Limited.

sales@impresspanels.co.nz 03 929 5641 www.impresspanels.co.nz

Impress Panels